

SV2250

DATA SHEET

POWER *:	36.6 kW @3000 rpm
MAX. TORQUE:	144.0 Nm @2000 rpm
NOISE LEVEL **:	75 dB(A)
WEIGHT *** :	341 Kg
DIMENSIONS (WxLxH):	71 x 90 x 83.5 cm
EMISSIONS COMPLIANCE:	2004/26 CE Stage III A
FUEL CONSUMPTION:	11,1 l/h

* **POWER:** ISO 3046 IFN

** **NOISE:** taken at 7 meters @2800 rpm without load

*** **WEIGHT:** oil and cooling liquid included

Measured technical data (+/- 1%) may be subject to changes.



STANDARD EQUIPMENT

- Base incorporated 40 liters fuel tank
- SAE 4 - 7" 1/2 flanging
- Electric accelerator with step by step key
- Control panel with tachometer and hour counter
- 12 V electric start
- Exhaust silencer

OPTIONAL ACCESSORIES

- Hydraulic pump adapter on 1st PTO
- Hydraulic pump adapter on 3rd PTO
- Cylindrical shaft extensions
- Industrial hand lever clutches
- 24 V electric start

Engine: Kohler KDW 2204
Cylinders: 4
Displacement: 2199 cm³



SV2250

- Bore (mm): 88
- Stroke (mm): 90.4
- Injection system: IDI
- Compression ratio: 22.5:1
- 4-stroke diesel engine with in-line cylinders
- Fluid-cooled with axial fan
- Indirect injection
- Geared distribution control
- Forced lubrication with vane pump on the crankshaft
- Cast iron cylinder head
- Cast iron engine block with re-borable integral liners