

## SV2550

### DATA SHEET

MAX POWER (NB)*:	36,4 kW @2600 rpm
CONTINUOUS POWER (NA)**:	32,7 kW @2600 rpm
MAX TORQUE*:	170 Nm @1500 rpm
NOISE LEVEL ***:	-
WEIGHT ****:	490 Kg
DIMENSION (WxLxH):	90 x 120 x 94 cm
EMISSIONS:	Stage III A
FUEL CONSUMPTION:	10,9 l/h

\*: ISO 3046 IFN

\*\* : ISO 3046 ICXN

\*\*\*: taken at 7 meters @ 2200 rpm without load

\*\*\*\*: oil and cooling liquid included

Measured technical data (+/-1%) may be subject to changes.



### STANDARD EQUIPMENT

- SAE 4 - 7" 1/2 flanging
- Electric accelerator with step-by-step key
- Control panel with tachometer and hour meter
- Emergency stop button
- 12 V electric start
- Exhaust silencer
- Electric fuel pump

### OPTIONAL ACCESSORIES

- Hydraulic pump adapter on 1<sup>st</sup> PTO
- Hydraulic pump adapter on 3<sup>rd</sup> PTO
- Cylindrical shaft extensions
- Industrial lever clutches

Engine:	Kohler KDI 2504 M
Cylinders:	4
Displacement (cm <sup>3</sup> ):	2482
Bore (mm):	88
Stroke (mm):	102
Injection system:	DI



### SV2550

- Four stroke diesel engine with in-line cylinders
- Liquid cooling
- 4 valves per cylinder
- Crankcase camshaft, timing gear
- Pushrods rocker arms timing with hydraulic valve tappets
- Cast iron crankcase with bed plate
- Cast iron cylinder head
- Engine electronic management
- Close-circuit crankcase breather
- Wastegate turbocharger
- Charge - air cooling