

Shell Helix High Mileage 15W-50

Synthetic technology motor oil - Helps to stop the ageing process in your engine

Shell Helix High Mileage helps protect high mileage engines from the formation of sludge and engine deposits. It contains anti-wear additives to help slow down wear.

Proud Drivers Choose Shell Helix

Main Applications

 Everyday motorway or city driving can mean severe conditions for engine oil. Shell Helix High Mileage helps to prolong the engine life of modern vehicles in demanding daily traffic conditions. Suitable for gasoline, diesel, gas or ethanol containing fuels.

Specifications, Approvals & Recommendations

- API SN/CF
- ACEA A3/B4
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell Lubematch at: http://lubematch.shell.com
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Shell Helix High Mileage 15W-50
Kinematic viscosity	@100°C	cSt	ASTM D445	18.12
Kinematic viscosity	@ 40°C	cSt	ASTM D445	136.30
Viscosity Index			ASTM D2270	149
MRV	@ -25°C	сР	ASTM D4684	28000 est
Density	@15°C	kg/m³	ASTM D4052	858.5
Flash Point		°C	ASTM D92	260
Pour Point		°C	ASTM D97	-39

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

Shell Helix High Mileage 15W-50 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.epc.shell.com

· Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.