The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020 Print Date 22.04.202		
SECTION 1. PRODUCT AND C	OMPANY IDENTIFICATION		
Product name	: Shell Omala S2 GX 68		
Product code	: 001F1172		
Manufacturer or supplier' Supplier Telephone Telefax	s details : TransDiesel Limited NZBN 9429036551132 533 Halswell Junction Road Christchurch 8042 New Zealand : 0800 848 267 (All Hours) :		
Emergency telephone number	: 0800 848 267 (All Hours)		
Recommended use of the Recommended use	chemical and restrictions on use : Gear lubricant.		

SECTION 2. HAZARDS IDENTIFICATION

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2017., Not classified as Dangerous Goods for transport, according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Hazard classification

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	Prevention:
	No precautionary phrases.
	Response:

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7

Revision Date 21.04.2020 No precautionary phrases. Print Date 22.04.2020

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90
Olefin sulphide	68511-50-2	Flam. Liq.4; H227	< 3
Alkyl polyamide	68784-17-8	Eye Irrit.2A; H319 Skin Irrit.2; H315 Skin Sens.1B; H317 Aquatic Acute3; H402	< 0.9

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7		Revision Date 21.04.2020	Print Date 22.04.2020
In case of eye contact	:	Flush eye with copious quantities of Remove contact lenses, if present ar rinsing. If persistent irritation occurs, obtain r	nd easy to do. Continue
If swallowed	:	In general no treatment is necessary are swallowed, however, get medica	3 1
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and sympton of black pustules and spots on the sl Ingestion may result in nausea, vom	kin of exposed areas.
Protection of first-aiders	:	When administering first aid, ensure appropriate personal protective equip incident, injury and surroundings.	, .
Notes to physician	:	Treat symptomatically.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.
emergency procedures Environmental precautions	:	Use appropriate containment to avoid environmental

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020 contamination. Prevent from spread ditches or rivers by using sand, ear barriers.	
	Local authorities should be advised cannot be contained.	t if significant spillages
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid acciden Prevent from spreading by making or other containment material. Reclaim liquid directly or in an absor Soak up residue with an absorbent suitable material and dispose of pro-	a barrier with sand, earth orbent. such as clay, sand or other
Additional advice	: For guidance on selection of perso see Section 8 of this Safety Data S For guidance on disposal of spilled this Safety Data Sheet.	sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact :	Strong oxidising agents.
Product Transfer :	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage	
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
Packaging material :	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice :	Polyethylene containers should not be exposed to high

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7

Revision Date 21.04.2020

Print Date 22.04.2020

temperatures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	WES-TWA (Mist)	5 mg/m3	NZ OEL
	Further informativapour.	ation: Sampled b	by a method that does	s not collect
Oil mist, mineral	Not Assigned	WES-STEL (Mist)	10 mg/m3	NZ OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020
Version 1.7	General Information: Define procedures for safe handling controls. Educate and train workers in the har measures relevant to normal activit product. Ensure appropriate selection, testin equipment used to control exposure equipment, local exhaust ventilation Drain down system prior to equipm maintenance. Retain drain downs in sealed storage subsequent recycle. Always observe good personal hyg washing hands after handling the n drinking, and/or smoking. Routinel protective equipment to remove con	g and maintenance of azards and control ties associated with this ng and maintenance of e, e.g. personal protective n. ent break-in or ge pending disposal or giene measures, such as naterial and before eating, y wash work clothing and ntaminants. Discard
	contaminated clothing and footwea Practice good housekeeping.	T that cannot be cleaned.

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks :	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020 Print Date 22	2.04.2020
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with pre for > 480 minutes where suitable gloves can be ident short-term/splash protection we recommend the same recognize that suitable gloves offering this level of pro may not be available and in this case a lower breakth time maybe acceptable so long as appropriate mainter and replacement regimes are followed. Glove thicknes a good predictor of glove resistance to a chemical as dependent on the exact composition of the glove mat Glove thickness should be typically greater than 0.35 depending on the glove make and model.	ified. For e but otection irough enance ess is not it is erial.
Eye protection	: If material is handled such that it could be splashed ir protective eyewear is recommended.	nto eyes,
Skin and body protection	 Skin protection is not ordinarily required beyond stand work clothes. It is good practice to wear chemical resistant gloves. 	dard
Thermal hazards	: Not applicable	
Environmental exposure co	rols	
General advice	: Take appropriate measures to fulfill the requirements relevant environmental protection legislation. Avoid contamination of the environment by following advice Section 6. If necessary, prevent undissolved materia being discharged to waste water. Waste water should treated in a municipal or industrial waste water treatm before discharge to surface water. Local guidelines on emission limits for volatile substa must be observed for the discharge of exhaust air con vapour.	given in I from J be nent plant nces
SECTION 9. PHYSICAL AND CH	IICAL PROPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: brown	

Coloal	. brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: -24 °C / -11 °FMethod: ISO 3016
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)
Flash point	: 236 °C / 457 °F Method: ISO 2592

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0.887 (15 °C / 59 °F)	
Density	: 887 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6(based on informatio	n on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 68 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	8.7 mm2/s (100 °C / 212 °F) Method: ISO 3104	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to b	e a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7		Revision Date 21.04.2020	Print Date 22.04.2020
Chemical stability	:	Stable.	
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.	
Conditions to avoid	:	Extremes of temperature and direct sun	light.
Incompatible materials	:	Strong oxidising agents.	
Hazardous decomposition products	:	No decomposition if stored and applied	as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020
Describe Material 's a		

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Alkyl polyamide:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification	
Highly refined mineral oil	No carcinogenicity classification.	

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

÷

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7

Revision Date 21.04.2020

Print Date 22.04.2020

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION			
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract). 		
Ecotoxicity			
Product:			
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.		
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.		
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.		
Toxicity to fish (Chronic toxicity)	: Remarks: Data not available		
Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available		
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available		

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020	
Persistence and degradability			
Product:			
Biodegradability		 Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment. 	
Bioaccumulative potential			
Product:			
Bioaccumulation	: Remarks: Contains components w bioaccumulate.	ith the potential to	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on ir products)	nformation on similar	
Mobility in soil			
Product:			
Mobility	 Remarks: Liquid under most enviro enters soil, it will adsorb to soil par mobile. Remarks: Floats on water. 		
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	 Does not have ozone depletion por ozone creation potential or global v is a mixture of non-volatile compor released to air in any significant qu conditions of use. Poorly soluble mixture., Causes ph organisms. Mineral oil does not cause chronic organisms at concentrations less the 	warming potential., Product nents, which will not be antities under normal hysical fouling of aquatic toxicity to aquatic	

SECTION 13. DISPOSAL CONSIDERATIONS

	Disposal methods	
	Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
		Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
		Disposal methods, including disposal of packaging, should be
~		000004000000

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020
	in accordance with the Hazardous Subs Notice 2017 and the Act.	stances (Disposal)
Contaminated packaging	Dispose in accordance with prevailing r to a recognized collector or contractor. the collector or contractor should be es Disposal should be in accordance with national, and local laws and regulations	The competence of tablished beforehand. applicable regional,
Local legislation Remarks	Disposal should be in accordance with national, and local laws and regulations	

SECTION 14. TRANSPORT INFORMATION

National Regulations

Land Transport Rule: Dangerous Goods 2012 -NZS 5433 Not regulated as a dangerous good

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

R-phrase(s)	:	Not classified.
S-phrase(s)	:	Not classified.

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7	Revision Date 21.04.2020	Print Date 22.04.2020
The regulatory information is not intended to be comprehensive this material.		ther regulations may apply to
	and Biological Exposure Indices N 12 Transport of Dangerous Goods	

Other international regulations

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H227	Combustible liquid.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H402	Harmful to aquatic life.	
Full text of other abbreviations		

Aquatic Acute	Short-term (acute) aquatic hazard
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,

The content and format of this SDS is in accordance with Hazardous Substances (Safety Data Sheets) Notice 2017

Shell Omala S2 GX 68

Version 1.7Revision Date 21.04.2020Print Date Date 21.04.2020Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inv Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United United Nations; UNRTDG - United Nations Recommendations on the Transport Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplay Materials Information System		Substance Inventory; TDG - trol Act (United States); UN - the Transport of Dangerous
Further information		
Training advice	: Provide adequate information, inst operators.	ruction and training for
Other information	: A vertical bar () in the left margin i from the previous version.	ndicates an amendment
Sources of key data used to	: The quoted data are from, but not	limited to, one or more

Sources of key data used to	: The quoted data are from, but not limited to, one or more
compile the Safety Data	sources of information (e.g. toxicological data from Shell
Sheet	Health Services, material suppliers' data, CONCAWE, EU
	IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NZ / EN