

Section 1. Identification of the material and the supplier

Product: Redex Fuel System Additive - PETROL

Product Code: RADD0014A
Product Use: Fuel Additive

Restriction of Use: Refer to Section 15

New Zealand Supplier: Filpro Automotive NZ Ltd

Address: 40 Firth St Drury

Auckland

Telephone: +64 9 2946752 Fax Number: +64 9 2946751

Emergency Telephone: 0800 764 766 (National Poison Centre)

Holt Lloyd International

Address: Barton Dock Road

Manchester M32 OYQ England

Inquires +44 161 866 4800

Date of SDS Preparation: 04 March 2021

Section 2. Hazards Identification

This substance is hazardous according to the HSNO (Minimum Degrees of Hazard) Regulations 2001

EPA Approval No: Fuel Additives (Flammable) - HSR002523

Pictograms







Flammable

e Toxic/Irritant

Chronic

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Category 3
6.1D (oral) (inhalation)	H304	Maybe fatal if swallowed and enters airways	Category 4
6.1D (dermal)	H312	Harmful in contact with skin.	Category 4
6.1D (inhalation)	H336	May cause drowsiness or dizziness.	Category 4
6.4A	H319	Causes serious eye irritation.	Category 2A
9.3C	H433	Harmful to terrestrial vertebrates.	

Prevention Code	Prevention Statement
P102	Keep out of reach of children.

P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P260	Do not breathe mist, vapours, or spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, and eye protection.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P363	Wash contaminated clothing before reuse.
P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you	
	unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position
130111310	comfortable for breathing.
P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P338	contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code	Storage Statement	
P405	Store locked up.	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.	

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum) hydrotreated	60-100	64742-48-9
heavy		
Distillates (petroleum), hydrotreated	1-5%	64742-47-8
kerosene		
Petroleum naphtha heavy aromatic	1-5%	64742-94-5
Naphthalene	<1%	91-20-3

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for 15 minutes. If eye irritation persists: Get

medical advice. Seek medical attention if you feel unwell.

If on Skin Wash with plenty of soap and water. Take off contaminated clothing and

wash before re-use. If skin irritation occurs: get medical advice/attention.

Seek medical attention if large area exposed.

If Swallowed Rinse mouth. DO NOT induce vomiting. Never give anything to the mouth

of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER (0800 764

766) or a doctor/physician if you feel unwell.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult or if you feel unwell.

Section 5. Fire Fighting Measures

Hazard Type	Flammable Liquid
Hazards from	Carbon monoxide, carbon dioxide.
combustion	
products	
Suitable	Use CO ₂ , dry powder, or chemical foam for extinction. Always choose
Extinguishing	fire-extinguishing media appropriate for surrounding materials.
media	
Precautions for	Wear full protective gear.
firefighters and	
special protective	
clothing	
HAZCHEM CODE	3Y

Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

CONTAINMENT TECHNIOUES

Stop spill at source. Dike area & contain. Remove all sources of ignition

SPILL CLEAN UP METHODS

Do not flush with water. Allow residues to evaporate

Do not contaminate water sources or sewer. Collect for reclamation or absorb in vermiculite, dry sand or similar material.

See Section 13 for disposal details.

Section 7. Handling and Storage

Precautions for Handling:

- Keep out of reach of children.
- Read label before use.
- Do not spray on or near an open flame or other ignition source.
- Do not breathe mist, vapours, or spray.
- Wash exposed skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Avoid release to the environment.
- Wear protective gloves, protective clothing, and eye protection.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Keep out of reach of children
- Store locked up in a well-ventilated place.
- Store away from sunlight. Keep cool.
- Store above freezing.

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA ppm	mg/m³	STEL ppm	mg/m³
Petroleum naphtha heavy aromatic	500			2000
Naphthalene	10	53	15	80

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

Engineering Controls

Ensure adequate ventilation is available.

Personal Protection

Eyes	Wear goggles with side shields. Avoid wearing contact lenses.
Hands and	Use suitable protective gloves if risk of skin contact. Wear appropriate
Skin	protective clothing to prevent skin contact.
Respiratory	If ventilation is poor, use appropriate cartridge respirator.

Section 9 Physical and Chemical Properties

Appearance	Red Liquid
Odour	Aromatic Hydrocarbons
Odour Threshold	Not applicable
pH	Not applicable
Boiling Point	130 C
Melting Point	Not applicable
Freezing Point	Not applicable
Flash Point	37 – 38 C (cc)
Flammability	Extremely Flammable
Upper and Lower Exposure	Not applicable
Limits	
Vapour Pressure	Not applicable
Vapour Density	Not applicable
Relative Density	Not applicable
Solubilities	Immiscible with water
Partition Coefficient:	Not applicable
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not applicable
Kinematic Viscosity	Not applicable
Particle Characteristics	Not applicable

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Conditions to Avoid	Keep away from heat, sparks, open flames and hot surfaces
Incompatible Materials	No specific material
Hazardous Decomposition	Carbon dioxide, carbon monoxide.
Products	

Section 11 Toxicological Information

Section 12. Ecotoxicological Information

HSNO Classes: 9.3C = Harmful to terrestrial invertebrates.

Persistence and degradability	Product is bio-degradable
Bioaccumulation	Product is bio-accumulating
Mobility in Soil	Contains substances that are water soluble and may spread
	in water systems
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Precautions: Dispose of waste according to Local regulations. Collected spillage and unused product must be placed in a sealable waste container for disposal through a disposal company.

Disposal methods to avoid: Do not allow product to enter sewers, streams, or waterways

Section 14 Transport Information

This product is classified as a Dangerous Good in NZ; NZS 5433:2012

Road and Rail Transport

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Air Transport

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Marine Transport

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.

Marine Pollutant Yes

Section 15 Regulatory Information

EPA Approval Code: Cleaning Products (Flammable) - HSR002528

HSNO Classification: 3.1C, 6.1D(oral), 6.1D(dermal), 6.1D(inh), 6.4A, 6.8B, 6.9A, 9.3C

HSNO Controls:

Trigger quantities for this substance:

	Trigger Quantity
Approved Handler	3000L awc
Location Certificate	3000L awc

Tracking Trigger Quantities	Not required
Signage Trigger Quantities	3000L awc
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	None

Section 16	Other Information	
Glossary		
AWC	Aggregate water capacity	
EC ₅₀	Median effective concentration.	
EEL	Environmental Exposure Limit.	
EPA	Environmental Protection Authority	
HSNO	Hazardous Substances and New Organisms.	
LC ₅₀	Lethal concentration that will kill 50% of the test organisms	
	inhaling or ingesting it.	
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.	
LEL	Lower explosive level.	
OES	Occupational Exposure Level	
OSHA	American Occupational Safety and Health Administration.	
TEL	Tolerable Exposure Limit.	
TLV	Threshold Limit Value-an exposure limit set by responsible	
	authority.	
UEL	Upper Explosive Level	
WEL	Workplace Exposure Limit	

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.

Disclaimer

This document has been issued by UCI Fram Ltd and serves as their Safety Data Sheet ('SDS'). It represents the appropriate safety and handling precautions for the product at the time of issue. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated., it does not provide any warranty as to accuracy or completeness. Please contact the country distributor, if further information is required.

Issue Date: 04 March 2021 Review Date: 04 March 2026